

FILLING THE APPLICATOR

Metered-Dose Topical Applicator



Transfer the desired amount of compounded cream into the UnoDose™ Applicator barrel using a spatula, ointment jar, or filling system.



For best results, remove air during filling.

Start with a small amount to fill the corners in the bottom of the barrel. Tap the bottom of the applicator on your palm or a countertop to settle the cream and remove air.



Add the remaining cream in several steps while continuing to tap the bottom of the applicator to settle the cream and remove air. Leave the top of the cream flat and smooth.



Put the applicator cap on the barrel and **push** downward to snap into place. The applicator cap will butt up against the ring on the barrel. Tap the bottom again and confirm that no air remains in the cream.



Prime to remove air. For a fast prime, use the prime tool supplied in each box. Push slowly until cream just comes out the holes, or the tool stops. NOTE: The short end of the tool leaves 32 usable milliliters in the applicator, the long end leaves 17.



Finish priming by turning the dosing knob several clicks until cream exits all holes smoothly and equally. **NOTE:** Be sure to leave the knob in a "lock" position, and not between clicks.



Wipe away the cream from the applicator cap, then lock the protective cover in place with a light push and clockwise turn. You will hear and feel a click.



Confirm the correct volume on the scale by reading at the blue line. NOTE: The scale shows the usable volume and clicks remaining, and excludes the residual volume of 1.5 milliliters.



Apply a **prescription label** to the barrel. **NOTE:** Do not cover the CLICKS scale.



Topi-CLICK | TEAM Technologies

300 Parkbrooke Place, Suite 210, Woodstock, GA 30189 877-870-8448 | info.TopiCLICK@teamtech.com

www.Topi-CLICK.com

